



Model Name Monitored PDU
Model Number CSAMz-1023-08-1

Input



Features

Current Meter	Digital True RMS Current Meter
Power Monitor	Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
Protocols	Http, SNMP, DHCP, UDP
Alarm Thresholds	User-Defined Alarm Thresholds for Warning and Overload
Event Alert	Email, Trap, Audible Alarm



Specification

General

Output	(8) IEC 320 C13
Input	(1) IEC 320 C14 attached power cord, 3 meters long
Protection	(1) 10 AMP Circuit Breaker

Communication

IP Address	(1) Yellow LED
PDU Status	(1) Green LED
Power Monitor	(1) RJ45 for Ethernet
Current	3 Digits Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2%+/-0.1AMP

Operation

Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	10 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	38 x 533 x 44 mm
Weight	2.5 kg

Regulatory Approvals

CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3
C-Tick AS/NZS CISPR 22: 2006



