



Model Name: Switched PDU

Model Number: CSAMz-1023/SW-08-1



Input

Features

- Current Meter** Digital True RMS Current Meter
- Power Monitor** Remote Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
- Protocols** Http, SNMP, DHCP, UDP
- Outlet Control** Individual Outlet Control
- Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload
- Event Alert** Email, Trap, Audible Alarm



Specification

General

- Output (8) IEC320 C13
- Input (1) IEC320 C20 Inlet, enclosed IEC320 C19 to C14 detachable power cord, 3 meters long
- Protection (1) 10 AMP Circuit Breaker

Communication

- IP Address (1) Yellow LED
- PDU Status (1) Green LED
- Power Status (8) Red LED
- Power Monitor (1) RJ45 for Ethernet
- Current 3 Digits Seven Segments for True RMS Meter
Range: 0A ~ 20 A
Resolution: 0.1A
Precision: +/-2%/+/-0.1AMP





Operation

Nominal Voltage	230V
Voltage	200V ~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	10 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	38 x 583 x 56 mm
Weight	2 kg

Regulatory Approvals

CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3
C-Tick AS/NZS CISPR 22: 2006

