



Input



Features

- Current Meter** Digital True RMS Current Meter
- Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
- Protocols** Http, SNMP, DHCP, UDP
- Alarm Thresholds** User-Defined Alarm Thresholds for Warning and Overload
- Event Alert** Email, Trap, Audible Alarm



Specification

General

Output	(7) IEC 320 C13 (1) IEC 320 C19
Input	(1) IEC 320 C20 attached power cord, 3 meters long
Protection	(1) 16 AMP Circuit Breaker

Communication

IP Address	(1) Yellow LED
PDU Status	(1) Green LED
Power Monitor	RJ45 for Ethernet
Current	3 Digits Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2% +/-0.1AMP

Operation

Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	16 Amp
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	38 x 533 x 44 mm
Weight	2.5 kg

Regulatory Approvals CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3
 C-Tick AS/NZS CISPR 22: 2006

