



CONCORDE

CONCORDE SOLUTIONS

MODEL NAME: CONCORDE SWITCHED PDU's

MODEL #: CSAMz-1623/SW-08-1



Features

Current Meter	Digital True RMS Current Meter
Power Monitor	Remote Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
Protocols	Http, SNMP, DHCP, UDP
Outlet Control	Individual Outlet Control
Alarm Thresholds	User-Defined Alarm Thresholds for Warning and Overload
Event Alert	Email, Trap, Audible Alarm



Specification

General

Output	(7) IEC320 C13 (1) IEC320 C19
Input	(1) IEC320 C20 Inlet, enclosed IEC320 C19 to C20 detachable power cord, 3 meters long
Protection	(1) 16 AMP Circuit Breaker

Communication

IP Address	(1) Yellow LED
PDU Status	(1) Green LED
Power Status	(8) Red LED
Power Monitor	(1) RJ45 for Ethernet
Current	3 Digits Seven Segments for True RMS Meter Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2%/+/-0.1AMP

Operation

Nominal Voltage	230V
Voltage	200V~ 240V full range
Frequency	50/60HZ full range
Max. Output Current	16 Amp (UL derated 12 Amp)
Temperature	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	38 x 583 x 56 mm
Weight	2 kg

Regulatory Approvals

UL 60950-1, UL Listed, CSA, cUL Listed, CB by UL
CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3
C-Tick AS/NZS CISPR 22: 2006

