



CONCORDE

Model Name: ATS

Model Number: ATSCS-1623K-10N1



Input



Description

230V, 16A, 10 Outlets, Dual Input, Redundant Power Protection, Remote kWh / Voltage Monitoring

Features

Meter

True RMS Current Meter, Voltage, Frequency, Power Factor, Active Power, Apparent Power, Total kWh, Sub-total kWh.

Power Monitor

Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

Protocols

Http, Https, SNMP, DHCP, UDP

Alarm Thresholds

User-Defined Alarm Thresholds for Warning and Overload

Event Alert

Email, Trap, Audible Alarm

Temp./Humidity

Option Accessory

Power Action

Automatic Transfer Switch



Specification

General

Output	(10) IEC320 C13
Input	(2) IEC320 C20 Inlet; Enclosed IEC320 C19 to C20 plugs 3 Meters

Communication

SSL Indication	(1) Yellow LED
DHCP Indication	(1) Green LED
Output Status	(2) Green LED
Input Status	(2) Green LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
Identification	1 Digits Seven Segments for Identification
Meter	3 Digits Seven Segments

Power Information

Voltage	+/- 2% @ 90V~260V
Active Power	+/- 2% @ 50W~5000W
Apparent Power	+/- 2% @ 50VA~5000VA
Frequency	+/- 2% @ 45~65Hz
Power Factor	+/- 0.02 @ 0.5~1.0
kWh	Range: 0.001kWh ~ 99999.999kWh Precision: +/-2% @ 50W~5000W, kh=1.0
Current	Range: 0A ~ 20 A Resolution: 0.1A Precision: +/-2%+/-0.1AMP

Operation

Nominal Voltage	200V ~240V
On-Line Voltage	180V~ 262V
Frequency	50/60Hz
Max. Output Current	16 Amp
Transfer Time	8~16ms
Operation Temp.	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	260 x 432 x 44.45 mm
Net Weight	5 kg

Regulatory Approvals	CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 FCC Part 15 Class A, ICES-003
-----------------------------	---